



# CLIPPARD BRASS AIR PILOT VALVES

These Normally-Open or Normally-Closed 2-Way and 3-Way valves incorporate an integral pilot actuator that provides a compact assembly and simple installation. The internal valving is identical to the MAV-2/3 or MAVO-2/3.

## FEATURES

- Maximum flow in a small package
- Spool type valves with Single or Double Air Pilots
- Available in 3-Way or 4-Way Configurations
- Well-suited for packaging, factory automation,

## SPECIFICATIONS

- **Medium:** Air, Water or Oil
- **Input Pressure:** PAV-2/3: 300 psig; PAVO-2/3: 150 psig max.
- **Air Pilot Pressure:** 15 psig min.
- **Air Flow:** PAV-2/3: 113 l/min @ 50 psig, 190 l/min @ 100 psig
- PAVO-2/3: 190 l/min @ 50
- **Mounting:** 5/8-32 thread or #4 screw
- **Materials:** Brass body, Nitrile seals, stainless steel stem & spring

## Normally-Closed Poppet Valves



(PAV-2P shown)

Port(s)	2-Way	3-Way
#10-32	PAV-2	PAV-3
1/8" NPT	PAV-2P	PAV-3P

## Normally-Open Spool Valves



(PAVO-2 shown)

Port(s)	2-Way	3-Way
#10-32	PAVO-2	PAVO-3
1/8" NPT	PAVO-2P	PAVO-3P